

CCP heat shrink tunnel



[Technical Parameters]

| Model name | CCP-R1000 | CCP-R1500 | CCP-R2000 | CCP-R3000 |
|-------------------|---------------|---------------|---------------|---------------|
| Max packing size | 500x320x200 | 700x320x200 | 1200x320x200 | 1500x320x200 |
| Shrink tunnel(mm) | 1000x400x250 | 1500x400x250 | 2000x400x250 | 3000x400x250 |
| Supply voltage | AC220 50/60HZ | | | |
| Belt Speed | 40 m/min | | | |
| Power(KW) | 12 | 15 | 18 | 22 |
| Machine size(mm) | 1600x660x1187 | 2100x660x1187 | 2600x660x1187 | 3600x660x1187 |

[Features]

1. Using high-pressure air type heat treatment, high stability, good shrinkage effect.
2. Conveyor roller is intensive galvanized roller, with High temperature resistant rubber sleeve makes it durability.
3. Variable frequency and multilayer insulation device to ensure adjustable temperature. Energy saving, environmental protection;
4. Microprocessor PID temperature controller to adjust the temperature, PID automatically estimate temperature, less temperature difference, no more than 1 degree
5. Choose our company CCP-H or CCP- L types automatic packaging machine, packaging better.
6. Suitable for PVC, POF and other kinds of films.

[Application]

For food, cosmetics, books, magazines, decorations, toys, hardware and other industries that required large quantities of shrink packing service.