

CCP standard shrink tunnel



[Technical Parameters]

| Model | CCP-RS116 | CCP-RS118 | CCP-RS180 |
|---------------------|---------------|---------------|---------------|
| Max packing size | 300*400*200 | 1200*400*200 | 2000*400*200 |
| Shrink stove(mm) | 800*400*200 | 1200*400*200 | 2000*300*200 |
| Supply voltage | AC380 50/60HZ | | |
| Power (KW) | 7.2 | 12 | 18 |
| Belt Speed | 30 m/min | | |
| Machinesize (mm) | 1200*720*1200 | 1800*720*1450 | 2600*720*1450 |

[Features]

1. Energy saving: adopt infrared radiation titanium heat pipe, heat faster, Energy savings of up to 40%;
2. Heated-air circulation: Thermal Shrinkage Oven adopts the design of hot air circulation, Improve the efficiency of heating.
3. Automatic control: adopt automatic temperature controlling system, more convenient thermoregulation;
4. Adopt variable speed motorproviding easy transport speed
5. Choose our company CCP-H or CCP- Ltypes automatic packaging machine, packaging better.
6. Suitable for PVC, POF and other kinds of films.

[Application]

For food, cosmetics, books, magazines, decorations, toys, hardware and other industries that required large quantities of shrink packing service.